

EBAKI

Horizontal boneless meat slicer

**EBAKI**



[www.ebakislicer.com](http://www.ebakislicer.com)



**VERSATILITY** is one of the most important EBAKI features



4 blades  
Distance between blades: 6 mm.

7 blades  
Distance between blades: 4.5 mm.

4 blades  
Distance between blades: 9 mm.

The individual cutting lanes and cutting sets work independently from each other, therefore, a different number of blades with a variety of thickness can be fitted at any one time. This enables versatility when using the machine.

## PERSONALIZED DESIGN

Dimaq is a company with a small, dynamic and flexible structure, which enables it to develop personal modifications as requested by the customer, according to their specific cutting requirements in a short period of time.

Some pieces of meat, such as streaky bacon, require wider cutting lanes, and our design team has adapted an EBAKI 3 that meets the requirement of the customer.



[www.ebakislicer.com](http://www.ebakislicer.com)

# The EBAKI horizontal slicer fillets boneless pork, beef, chicken and turkey evenly, thus achieving parallel sliced fillets.

The product is transported to the cutting area via a lower and an upper conveyor belt which holds and flattens the product during filleting, ensuring minimal waste.

The blades move in opposite directions to each other, so this prevents the product from moving, and provides a very even cut result.

## EBAKI 1

Productivity: 2.000 kg / hour  
Possible to fit up to 10 blades  
Maximum product width: 135 mm / lane.  
Maximum product height: 65 mm  
Cutting thickness: from 3.5 mm  
Cutting heads included: 1  
Variable blade and belt speed  
Measurements: 2350 x 775 x 1350 mm.  
Weight: 450 kg.  
Electrical connection: 380+N+T  
Output: 1,5 kW.



## EBAKI 2

Productivity: 4.000 kg. / hour  
Possible to fit up to 10 blades  
Maximum product width: 135 mm / lane  
Maximum product height: 65 mm  
Cutting thickness: from 3.5 mm  
Cutting heads included: 2  
Variable blade and belt speed  
Measurements: 2350 x 1075 x 1350 mm  
Weight: 550 Kg.  
Electrical connection: 380+N+T  
Output: 2.0 kW.



## EBAKI 3

Productivity: 6.000 kg. / hour  
Possible to fit up to 10 blades  
Maximum product width: 135 mm / lane.  
Maximum product height: 65 mm  
Cutting thickness: from 3,5 mm  
Cutting heads included: 3  
Variable blade and belt speed  
Measurements: 2350 x 1375 x 1350 mm  
Weight: 660 Kg.  
Electrical connection: 380+N+T  
Output: 2.0 kW.



EBAKI

**EBAKI**  
www.ebakislicer.com

**DIMAQ** s.l.  
maquinaria de alimentación

Polígono Txiplau - Pabellón 9  
20280 Hondarribia - (Gipuzkoa) - Spain  
Tel: (0034) 943 64 10 22 - Fax: (0034) 943 64 11 33  
www.dimaq.net

